

KODAK Media Setup Reference for NJ 1000i Printer

Qi Dye		
	Recommended Printer Heater Setting (1)	Recommended Print Mode*
Photographic		
Kodak Rapid-Dry Photographic Glossy Paper / 200g (8 mil)	2	Production (3 Bi 10)
Kodak Rapid-Dry Photographic Satin Paper / 200g (8 mil)	2	Production (3 Bi 10)
Kodak Premium Photographic Glossy Paper / 270g (10 mil)	4	Production (3 Bi 10)
Kodak Premium Photographic Glossy Paper / 180g (8 mil)	4	Production (3 Bi 10)
Kodak Premium Photographic Satin Paper / 180g (8 mil)	6	Production (3 Bi 10)
Kodak Premium Photographic Matte Paper / 180g (8 mil)	4	Production (3 Bi 10)
Kodak Economy Photographic Glossy Paper / 160g (6 mil)	10	Production (3 Bi 10)
Kodak Economy Photographic Satin Paper / 160g (6 mil)	Fans Only	Production (3 Bi 10)
Coated		
Kodak Coated Matte Print Paper / 140g (6 mil)	Fans Only	Fine (4 Bi 10)
Kodak Coated Matte Print Paper / 90g (4 mil)	Fans Only	Fine (4 Bi 10)
Kodak Self-Adhesive Coated Matte Print Paper / 100g (7 mil)	Fans Only	Production (3 Bi 10)
Film		
Indoor:		
Kodak Premium Backlit Film (7 mil)	10 (No Fans)	Production (3 Bi 10)
Kodak Premium White Film (5 mil)	6	Production (3 Bi 10)
Reverse Print Backlit VS (5 mil)	10	Fine (4 Bi 10)
Kodak Poly Poster Glossy (7 mil)	10	Production (3 Bi 10)
Kodak Poly Poster Satin (7 mil)	10	Production (3 Bi 10)
Indoor/Outdoor:		
Kodak Reverse Print Backlit Film (6 mil)	2	User Defined (6 Bi 10)
Kodak Water-Resistant Backlit Film (8 mil)	2	Production (3 Bi 10)
Kodak Water-Resistant Poly Poster Matte (8 mil)	2	User Defined (8 Bi 10)
Kodak Water-Resistant Self-Adhesive Poly Poster Matte (9 mil)	2	User Defined (8 Bi 10)
Kodak Self-Adhesive Glossy Poly Poster (120g)	10	Production (3 Bi 10)
Kodak Self-Adhesive Matte Poly Poster (120g)	10	Production (3 Bi 10)
Vinyl		
Kodak GO Water-Resistant Scrim Vinyl	6	User Defined (6 Bi 10)
Kodak GO Water-Resistant Self-Adhesive Vinyl	2	User Defined (6 Bi 10)
KODAK Water-Resistant Removable Vinyl	2	User Defined (8 Bi 10)
KODAK Water-Resistant Scrim Banner	2	User Defined (6 Bi 10)
Specialty		
Fine Art:		
Kodak Artists' Semigloss Canvas (20 mil)	2	Production (3 Bi 10)
Kodak Matte Canvas (19 mil)	Fans Only	Production (3 Bi 10)
Indoor/Outdoor:		
Kodak GO Banner/Dupont® Tyvek material (9 mil)	2	User Defined (6 Bi 10)
Kodak GO Wet Strength Paper (11 mil)	2	User Defined (6 Bi 10)
Kodak GO Polyethylene Banner (10 mil)	2	User Defined (6 Bi 10)
Kodak Water-Resistant Reinforced Flex Banner (15 mil)	2	User Defined (8 Bi 10)

(1): Based on room conditions of 23C/50% RH.

*: Recommended mode for photo image quality

3 Bi 10 = 3 pass, bidirectional, 10 speed

4 Bi 10 = 4 pass, bidirectional, 10 speed

6 Bi 10 = 6 pass, bidirectional, 10 speed

8 Bi 10 = 8 pass, bidirectional, 10 speed

KODAK Media Setup Reference for NJ 1000i Printer

Qi Pigment		
	Recommended Printer Heater Setting (1)	Recommended Print Mode*
Photographic		
Kodak Rapid-Dry Photographic Glossy Paper / 200g (8 mil)	2	Fine (4 Bi 10)
Kodak Rapid-Dry Photographic Satin Paper / 200g (8 mil)	2	Fine (4 Bi 10)
Coated		
Kodak Coated Matte Print Paper / 140g (6 mil)	Fans Only	User Defined (6 Bi 10)
Kodak Self-Adhesive Coated Matte Print Paper / 100g (7 mil)	Fans Only	Fine (4 Bi 10)
Film		
Indoor/Outdoor:		
Kodak Reverse Print Backlit Film (6 mil)	2	User Defined (6 Bi 10)
Kodak Water-Resistant Backlit Film (8 mil)	2	Fine (4 Bi 10)
Kodak Water-Resistant Poly Poster Matte (8mil)	2	User Defined (6 Bi 10)
Kodak Water-Resistant Self-Adhesive Poly Poster Matte (9 mil)	2	User Defined (6 Bi 10)
Vinyl		
Kodak GO Water-Resistant Scrim Vinyl	6	User Defined (6 Bi 10)
Kodak GO Water-Resistant Self-Adhesive Vinyl	2	User Defined (6 Bi 10)
KODAK Water-Resistant Removable Vinyl	2	User Defined (8 Bi 10)
KODAK Water-Resistant Scrim Banner	2	User Defined (6 Bi 10)
Specialty		
Fine Art:		
Kodak Artists' Semigloss Canvas (20 mil)	2	Production (3 Bi 10)
Kodak Matte Canvas (19 mil)	Fans Only	Fine (4 Bi 10)
Indoor/Outdoor		
Kodak GO Banner/Dupont® Tyvek material (9 mil)	2	User Defined (6 Bi 10)
Kodak GO Wet Strength Paper (11 mil)	2	User Defined (6 Bi 10)
Kodak GO Polyethylene Banner (10 mil)	2	User Defined (6 Bi 10)
Kodak Water-Resistant Reinforced Flex Banner (15 mil)	2	User Defined (6 Bi 10)

(1): Based on room conditions of 23C/50% RH.

*: Recommended mode for photo image quality

3 Bi 10 = 3 pass, bidirectional, 10 speed

4 Bi 10 = 4 pass, bidirectional, 10 speed

6 Bi 10 = 6 pass, bidirectional, 10 speed

8 Bi 10 = 8 pass, bidirectional, 10 speed